

# E-17



▶ FEATURES

- Exceptionally elegant exterior
- Stylish rear side design
- Swift 3ms response time
- High 300 brightness
- Crisp 800:1 contrast ratio
- NeoV Optical Glass™
- Dual digital and analog inputs\*
- Built-in speakers with headphone jack
- Auto-adjustment for optimal settings
- Intuitive OSD with key lock function
- Kensington® security socket
- VESA standard wall mount



▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	17.0" (432mm)
	<b>Max. Resolution</b>	SXGA 1280 x 1024
	<b>Pixel Pitch</b>	0.264mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	800:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	160°/160° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	3ms (GTG)
Input	<b>Frequency (H/V)</b>	H: 24kHz - 80kHz V: 56Hz - 75Hz
	<b>Max. Pixel Clock</b>	135MHz
Input	<b>Life Time</b>	50,000hrs (Minimum)
	<b>Analog</b>	15-Pin D-Sub
Input	<b>Digital*</b>	29-Pin DVI-D
	<b>Audio In</b>	3.5mm Audio Line-in
Audio	<b>Audio Out</b>	3.5mm Headphone Jack
	<b>Speaker</b>	1W x 2
Connector	<b>Power</b>	3-Pin AC Plug
NeoV Optical Glass	<b>Thickness</b>	3.0mm (0.18")
	<b>Reflection Rate</b>	<1%
	<b>Transmission Rate</b>	>96%
	<b>Hardness</b>	>6H (MOH's Rating)
Tilt	<b>Tilt</b>	+5° ~ +25°
Mounting	<b>VESA FPMPI</b>	Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, GOST, WEEE, RoHS
	<b>VESA</b>	DDC 1/2B, DPMS
Power	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off)
	<b>Dimensions</b>	<b>Net (W x H x D)</b> 400 x 390 x 171mm (15.8" x 15.4" x 6.7") <b>Packing (W x H x D)</b> 555 x 580 x 171mm (21.9" x 22.8" x 6.7")
Weight	<b>Net Weight</b>	6.2Kg (13.6 lbs)
	<b>Gross Weight</b>	8.0Kg (17.7 lbs)
Packing	<b>1 Pallet</b>	42 Cartons
	<b>20' Container</b>	420 Sets
	<b>40' Container</b>	924 Sets

\*DVI input is an optional function

All specifications are subject to change without prior notice